Connectors for Ultrasound Scanning System

Interface for LCD **Control Board** 4 Interface for Probe Pitch: 0.8mm

1 Control Board Function MAX



FX18 10+Gbps High Speed **Transmissions** No. of Pos.: 40-180



10+Gbps High Speed **Transmissions** Pitch: 0.8mm No. of Pos.: 10-120

FH41

Transmissions

Shielded FFC

Pitch: 0.5mm



XG1 16+Gbps High Speed Transmissions Mezzanine Connector Pitch: 0.5mm No. of Pos.: 78-260



Transmissions Pitch: 1.0mm **High Speed Transmissions**

2.5Gbps High Speed

2 Interface for LCD



FH48 3.75Gbps High Speed 3.75Gbps High Speed **Transmissions** Vertical Connection Shielded FFC



GT17H Positive Lock USB2.0

3 USB

4 Interface for Probe

EX80

Connector

Pitch: 0.6mm

Shielded Coplanar

No. of Pos.: 54,100





FX10 Pitch: 0.5mm Stacking Height: 4-13mm No. of Pos.: 80-168



FX11 Pitch: 0.5mm Stacking Height: 2-3mm No. of Pos.: 80/8-140/14 (Signal Pos./ Ground Pos.) 96-168 (Without Ground Plate)



EX Low Insertion Interface No. of Pos.: 280



Pitch: 0.5mm

FH28K **FPC Connector** Pitch: 0.5mm No. of Pos.: 10-80



DF80 Micro Coaxial Connector No. of Pos.: 30, 40, 50 Applicable Cable: 32-36 AWG (Discreet Cable) 40-46 AWG (Thin Wire Coaxial Cable)



DF81 Micro Coaxial Connector No. of Pos.: 30, 40, 50 Applicable Cable: 34-36 AWG (Discreet Cable) 40-46 AWG (Thin Wire Coaxial Cable)



3 USB