

Connectors for UPS (Uninterruptible Power Supply)



Power Line

Cable Connection



DF60 EnerBee

Small and High Current
1-6pos. 65A Max. (UL Standard)
1000V AC, 8-12 AWG



EF2 ZERO SCREW™

One Action Positive Lock
Applicable Cable:
1.25sq-200sq
400A Max. with 200sq wire



EM12M

Snap-in Lock
Single Power Pos.
130A Max., 1000V AC/DC



PS3C

210A Max. with 50sq wire
1000V AC/DC
Right Angle Plug
Saves Space During Wiring

Signal Line

Board-to-Board



FX30B FunctionMAX

Misalignment Absorption
Right Angle, Coplanar, Parallel
2-5pos., 25A Max.
600V AC/DC Max. (7.62mm Pitch)



PS3

Power: 210A Max.
with 50sq wire
Signal: 1A
1000V AC/DC
High Current Feed
Signal Hybrid




PS4

High Current
400A Bus Bar Thickness:
3mm or 0.125 inch (3.175mm)
430A Bus Bar Thickness:
6mm or 0.25 inch (6.35mm)
Floating Design



MQ221

105A Max.
(Ambient Temp. of 25°C)
Signal: 1A
Power: 600V AC/DC
Signal: 200V AC/DC
Power/Signal Hybrid



MDF7

(Freely Set Distance
Between Boards)
Bottom Entry
2.54mm Pitch
3A, 250V



FunctionMAX

FX20

Floating Design
0.5mm Pitch
15-30mm Height
20-140pos.
0.5A, 50V AC

Cable Connection



HIF3M*W

MIL Standard
2.54mm Pitch
10-64pos.
1A, 200V



FX2B

1.27mm Pitch
20-120pos.
0.5A, 125V AC



ZE05

Meets Automotive Spec.
2mm Pitch
2-24pos.
5A Max., 60V AC
Applicable Cable:
0.3-0.5sq



SignalBee

DF51

Positive Lock
2mm Pitch, 1, 2 Rows
2-30pos.
3A, 250V AC/DC
22-30 AWG



SignalBee

DF51K

Center Lock
2mm Pitch, 1, 2 Rows
2-30pos.
3A, 250V AC/DC
22-30 AWG



SignalBee

DF50/DF50A

Positive Lock,
Coplanar, Right Angle
1mm Pitch
2-16pos. (Single Row)
20, 30, 40, 50pos. (Double Row)
1A Max., 100V AC/DC
26-32 AWG



SignalBee

DF62


Slim Inline Connector
2-7, 13, 24pos.
4A Max. 250V AC/DC
22-30 AWG



FH OneAction

FH63S

One Action Lock
FPC/FFC/Shield FPC Compatible
0.5mm Pitch
2.8mm Height
10-40pos.
0.5A, 50V AC/DC



FH

FH52K

Meets Automotive Spec.
0.5mm Pitch
Front Flip
2mm Height
6-80pos.
0.5A, 50V AC/DC